

TASK	EWP					
HAZARDS	Flying debris		Heat / cold		Electricity	\boxtimes
	Cuts / laceration		Dust		Tip Over	\boxtimes
	Pinch / crush		Noise / vibration		Plant interaction	\boxtimes
	High pressure		Falling	\boxtimes	Entrapment	\boxtimes
PPE REQUIRED						

PRE-START CHECKS

- 1. Inspect the EWP for any visible damage, leaks, or defects.
- 2. Complete all pre-start checks as per manufacturer's guidelines.
- 3. Check the stability of the ground and ensure it can support the weight of the EWP.
- 4. Verify that all safety features, such as guardrails and emergency stop buttons, are functional.
- 5. Confirm that all controls and systems are operational by performing a test lift and lowering.

SAFE OPERATING PROCEDURE

- 1. Ensure personnel are competent and authorized.
- 2. Ensure personnel are fit for duty and not impaired by drugs or alcohol.
- 3. Do not use a mobile phone while operating and always wear your seatbelt.
- 4. Operate at a safe speed and maintain exclusion zones around people, powerlines, and other hazards (use spotters if necessary).
- 5. Beware of uneven or sloping ground.
- 6. Use the provided harness and attach to the designated anchor point before ascending.
- 7. Lower the platform completely and secure it before exiting the EWP.

POST-OPERATION PROCEDURE

- 1. Lower the platform to the ground and turn off the EWP.
- 2. Perform a final visual inspection for any damage or debris.
- 3. Secure the EWP and return it to the designated storage area.
- 4. Report any issues or incidents encountered during operation to the appropriate personnel.