


# SOP (GRAIN CART)

SS-WHS-SAF-000

Authorised By:

Rev 1 [Publish Date]



<b>TASK</b>	Grain cart					
<b>HAZARDS</b>	Flying debris	<input type="checkbox"/>	Heat / cold	<input type="checkbox"/>	Electricity	<input type="checkbox"/>
	Cuts / laceration	<input type="checkbox"/>	Exposure	<input type="checkbox"/>	Struck-by	<input checked="" type="checkbox"/>
	Pinch / crush	<input checked="" type="checkbox"/>	Noise / vibration	<input type="checkbox"/>	Plant interaction	<input type="checkbox"/>
	High pressure	<input type="checkbox"/>	Falling	<input type="checkbox"/>	Entrapment	<input checked="" type="checkbox"/>
<b>PPE REQUIRED</b>						

## PRE-START CHECKS

1. Inspect the grain cart for any visible damage, leaks, or defects.
2. Check tire pressure and condition of tires.
3. Ensure all safety decals and warning signs are visible and legible.
4. Verify that hitch points are secure and properly attached to the tractor.

## SAFE OPERATING PROCEDURE

1. Ensure all personnel are trained and authorized to operate the grain cart.
2. Wear appropriate personal protective equipment (PPE), including gloves, eye protection, and hearing protection.
3. Follow manufacturer's guidelines for safe operation, including load capacity and speed limits.
4. Be aware of surroundings and hazards, such as uneven terrain, obstacles, and overhead power lines.
5. Use caution when turning, reversing, or operating near edges to prevent accidents.

## POST-OPERATION PROCEDURE

1. Park the grain cart in a designated area and turn off the engine.
2. Lower any augers or other moving parts and secure them properly.
3. Perform a final visual inspection for any damage or debris.
4. Clean the grain cart and remove any residue or debris to prevent corrosion and damage.
5. Report any issues or incidents encountered during operation to the appropriate personnel.