

SOP (PLANTER)

SS-WHS-SAF-000

Authorised By:

Rev 1 [Publish Date]



TASK	Planter					
HAZARDS	Flying debris	<input type="checkbox"/>	Heat / cold	<input type="checkbox"/>	Electricity	<input type="checkbox"/>
	Cuts / laceration	<input checked="" type="checkbox"/>	Exposure	<input type="checkbox"/>	Struck-by	<input checked="" type="checkbox"/>
	Pinch / crush	<input checked="" type="checkbox"/>	Noise / vibration	<input type="checkbox"/>	Plant interaction	<input type="checkbox"/>
	High pressure	<input type="checkbox"/>	Falling	<input type="checkbox"/>	Entrapment	<input checked="" type="checkbox"/>
PPE REQUIRED						

PRE-START CHECKS

1. Inspect the planter for any visible damage, worn-out parts, or loose bolts.
2. Check seed and fertilizer bins for proper alignment and secure fastening.
3. Ensure all safety guards and shields are in place and functioning properly.
4. Verify that all connections and hitch points are secure.

SAFE OPERATING PROCEDURE

1. Ensure all personnel are trained and authorized to operate the planter.
2. Wear appropriate personal protective equipment (PPE), including gloves, eye protection, and hearing protection.
3. Follow manufacturer's guidelines for safe operation, including speed and depth settings.
4. Be aware of surroundings and hazards, such as uneven terrain, obstacles, and buried utilities.
5. Use caution when turning, reversing, or operating near edges to prevent accidents.

POST-OPERATION PROCEDURE

1. Park the planter in a designated area and turn off the engine.
2. Lower the planter to the ground and disengage all hydraulic controls.
3. Perform a final visual inspection for any damage or debris.
4. Clean the planter and remove any residue or debris to prevent corrosion and damage.
5. Secure the planter and store any detachable parts or accessories properly.
6. Report any issues or incidents encountered during operation to the appropriate personnel.